

IECEx Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 15.0055X

Issue No: 1

Certificate history:

Status:

Current

Issue No. 1 (2019-04-18) Issue No. 0 (2015-09-02)

Page 1 of 4

Date of Issue:

2019-04-18

Applicant:

Gastron Co. Ltd.

23 Gunpocheomdansaneop 1-ro,

Gunpo-Si, Gyeonggi-Do,

15881

Korea, Republic of

Equipment:

Type GTD-5000F(CT) & GTD-5000F(IR) Gas Detector Units

Optional accessory:

Type of Protection:

Flameproof

Marking:

Ex d IIB+H₂ T6* Gb (Ta -20°C to +60°C)

* alternative marking of T5 (Ta -20°C to +70°C) is also permitted

Approved for issue on behalf of the IECEx

R S Sinclair

Certification Body:

Position:

Technical Manager

Signature:

(for printed version)

Date:

Certification Manager

M POWNEY

- 1. This certificate and schedule may only be reproduced in full.
- 2. This certificate is not transferable and remains the property of the issuing body.
- 3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

SGS Baseefa Limited Rockhead Business Park Staden Lane Buxton, Derbyshire, SK17 9RZ **United Kingdom**





IECEx Certificate of Conformity

Certificate No:

IECEx BAS 15.0055X

Issue No: 1

Date of Issue:

2019-04-18

Page 2 of 4

Manufacturer:

Gastron, Co. Ltd.

23 Gunpocheomdansaneop 1-ro, Gunpo-Si, Gyeonggi-Do,

15881

Korea, Republic of

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2011

Explosive atmospheres - Part 0: General requirements

Edition:6.0

IEC 60079-1: 2007-04

Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"

Edition:6

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

CN/CQM/ExTR15.0034/00

Quality Assessment Report:

NL/DEK/QAR19.0002/00



IECEx Certificate of Conformity

Certificate No:

IECEx BAS 15.0055X

Issue No: 1

Date of Issue:

2019-04-18

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Type GTD-5000F(CT) & GTD-5000F(IR) Gas Detector Units comprise a cylindrical enclosure cast in aluminium alloy complete with a threaded cover incorporating a glass window.

A gas sampling system is located within the enclosure, including a gas sensor and pump assembly, with sintered flame arrestor plugs at both the gas inlet and gas outlet. The sensor may be a cartridge type unit (CT) or infrared (IR) as shown in the model designation. The unit may also contain a variety of processing and display electronics/PCB's, including options for an alarm relay, a 4-20mA output and an Rs-485 communication signal.

A cable entry hole threaded M20 or M25 (or NPT equivalent) is provided to facilitate electrical connection via a suitable equipment certified flameproof cable entry device.

SPECIFIC CONDITIONS OF USE: YES as shown below:

- 1. Contact the original manufacturer for information on the flameproof joint dimensions, if required during installation, maintenance or repair.
- 2. This equipment is for use at atmospheric levels of oxygen and pressure only (i.e. ≤ 21% Oxygen v/v, and 80 to 110kPa [0.8 to1.1 bar]). Sample flow control is permitted on the inlet only, with the outlet venting to atmospheric pressure (or lower).



IECEx Certificate of Conformity

Certificate No:

IECEx BAS 15.0055X

Issue No: 1

Date of Issue:

2019-04-18

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

This document permits existing information (for example on Schedule Drawings) to be replaced by the revised certificate holders address. No other changes may be made to the certified design

File Reference: 19/0174