

## Smart Diffusion Flammable Gas Detector

# GTD-2000Ex



### Features

- This detector is specialized for detecting combustible gases.
- It is designed with an explosion-proof structure, ensuring there is no risk of secondary explosions.
- Equipped with a display for easy monitoring and calibration.
- KFI-approved model integrated with the GTC-210A control panel.
- HART communication is supported.
- Remote calibration and program settings can be configured using a magnetic bar.
- The calibration process is simple enough to be completed by a single operator.
- Compatible with explosion proof warning lights (GTL-100) attached to the detector.

### Accessories



Cable gland



GTL-100



Rain cover



HART Module



Splash guard



Collecting cone

## Sensor Specification

\* = Refer to Toxic gas measuring range

| Measuring method | Catalytic cell      | Hot wire semiconductor cell | Thermal conductivity cell |
|------------------|---------------------|-----------------------------|---------------------------|
| Measuring gas    | Flammable gas       | Flammable gas               | Flammable gas             |
| Measuring range  | 0 ~ 100% LEL        | 0 ~ 2000ppm                 | 0 ~ 100% Vol              |
| Response time    | < 15sec / 90% scale | < 15sec / 90% scale         | < 15sec / 90% scale       |
| Material         | SUS316              | SUS316                      | SUS316                    |

## Detector Specification

| Measuring type          | Diffusion type   |
|-------------------------|--|
| Accuracy                | ±3% / Full scale   |
| Parameter control       | Non intrusive control with a Magnet bar (Calibration, Maintenance)                                       |
| Operation mode display  | 1-LED (Power)  |
| Measuring value display | LCD display (Built in back light 2-Line, 8 Characters) / OLED type (Option)                              |
| Output signal           | Analog : 4-20mA Analog output / Maintenance signal : 4mA / Calibration signal : 3mA / Fault signal : 0mA |
| Material                | Aluminium alloy or Stainless steel   |
| Cable entry thread      | Standard : PF 3/4"   Option : PF 1/2" , M20 x 1.5P , M25 x 1.5P , NPT 1/2" , NPT 3/4"                    |
| Mounting type           | 2" Pole mount, Wall mount  |
| Operating temperature   | -40°C ~ 80°C   |
| Operating humidity      | 5 ~ 99% RH (Non-condensing)  |
| Dimensions              | 136(W) x 166(H) x 110(D) mm  |
| Weight                  | 1.4Kg (Aluminium alloy)   3.1Kg (Stainless steel)  |

## Detector Certification

|                                      |         |  |   |          |   |
|--------------------------------------|---------|--|---|----------|---|
| Explosion-Proof Certification        | KCs     | Korea Explosion Proof Certification            | Ex tD A21 IP66 T85°C, Ex d IIC T6, T5, T4 |          |   |
|                                      | ATEX    | European Explosion Proof Certification         | Ex db IIC Gb T6, T5, T4                   |          |   |
|                                      | IECEX   | International Explosion Proof Certification    | Ex db IIC Gb T6, T5, T4                   |          |   |
|                                      | NEPSI   | China Explosion Proof Certification            | Ex db IIC T5 Gb                           |          |   |
|                                      | UL      | U.S. Explosion Proof Certification             | Class I, Division 1, Groups A,B,C,D       |          |   |
|                                      | PESO    | India Explosion Proof Certification            | Ex db IIC T6/T5/T4 Gb                     |          |   |
|                                      | TIIS    | Japan Explosion Proof Certification            | Ex db IIC Gb                              |          |   |
|                                      | TRCU ex | Russian Explosion Proof Certification          | 1Ex d IIC T6...T4 Gb X                    |          |   |
|                                      | TS      | Taiwan Explosion Proof Certification           | Ex db IIC Gb T6/T5/T4                     |          |   |
|                                      | ECAS Ex | UAE Explosion Proof Certification              | Ex db IIC Gb T6/T5/T4                     |          |   |
| Classification Society Certification | KR      | Korea Classification Society Certification     | Other Certifications                      | HART     | Communication Protocol Certification        |
|                                      | MED     | European Classification Society Certification  |   | SIL2     | Safety Integrity Certification              |
|                                      | ABS     | U.S. Classification Society Certification      |   | CE(EMC)  | European Electromagnetic Certification      |
|                                      | BV      | France Classification Society Certification    |   | CPA      | China Measuring Instrument Certification    |
|                                      | DNV     | Norwegian Classification Society Certification |   | -        | Thailand Ministry of Energy Certification   |
|                                      | CCS     | China Classification Society Certification     |   | KC       | Korea Electromagnetic Certification         |
|                                      | RS      | Russian Classification Society Certification   |   | KFI      | Korea Fire Safety Certification             |
|                                      | LR      | UK Classification Society Certification        |   | PAC      | Russia Measuring Instrument Certification   |
|                                      | RINA    | Italian Classification Society Certification   |   | CE(RoHS) | European Hazardous Substances Certification |